


Codice Clig. No.	R Rigidità Rate N/mm	XLL 25%		Max 37.5%		L <sub>0</sub> Lungh. libera Free length mm
		S <sub>1</sub> Corsa Stroke mm	F <sub>1</sub> Carico Load N	S <sub>2</sub> Corsa Stroke mm	F <sub>2</sub> Carico Load N	
(D) Sede • Housing Ø mm 10 (d) Spina • Rod Ø mm 5						
Sezione filo • Wire section <b>1,8 x 1,2</b>						
2S10025	16,0	6,3	100	9,4	150	25
2S10032	13,0	8,0	104	12,0	156	32
2S10038	11,9	9,5	113	14,3	170	38
2S10045	10,3	11,0	113	16,5	170	44
2S10050	8,9	12,8	113	19,1	170	51
2S10065	7,5	16,0	120	24,0	180	64
2S10075	6,2	19,0	118	28,5	177	76
2S10303	1,6	76,3	122	114,4	183	305
(D) Sede • Housing Ø mm 12,5 (d) Spina • Rod Ø mm 6,3						
Sezione filo • Wire section <b>2,5 x 1,7</b>						
2S13025	30,0	6,3	188	9,4	281	25
2S13032	24,8	8,0	198	12,0	298	32
2S13038	21,4	9,5	203	14,3	305	38
2S13045	18,0	11,0	198	16,5	297	44
2S13050	15,5	12,8	198	19,1	296	51
2S13065	12,1	16,0	194	24,0	290	64
2S13075	10,2	19,0	194	28,5	291	76
2S13090	8,4	22,3	187	33,4	280	89
2S13101	7,1	25,5	181	38,3	272	102
2S13303	2,4	76,3	183	114,4	275	305
(D) Sede • Housing Ø mm 16 (d) Spina • Rod Ø mm 8						
Sezione filo • Wire section <b>3,2 x 2,0</b>						
2S16025	49,4	6,3	309	9,4	463	25
2S16032	38,5	8,0	308	12,0	462	32
2S16038	33,9	9,5	322	14,3	483	38
2S16045	30,0	11,0	330	16,5	495	44
2S16050	26,4	12,8	337	19,1	505	51
2S16065	20,5	16,0	328	24,0	492	64
2S16075	17,8	19,0	338	28,5	507	76
2S16090	15,2	22,3	338	33,4	507	89
2S16101	13,5	25,5	344	38,3	516	102
2S16115	12,0	28,8	345	43,1	518	115
						127
						152
2S16303	4,3	76,3	328	114,4	492	305

Codice Clig. No.	R Rigidità Rate N/mm	XLL 25%		Max 37.5%		L <sub>0</sub> Lungh. libera Free length mm
		S <sub>1</sub> Corsa Stroke mm	F <sub>1</sub> Carico Load N	S <sub>2</sub> Corsa Stroke mm	F <sub>2</sub> Carico Load N	
(D) Sede • Housing Ø mm 20 (d) Spina • Rod Ø mm 10						
Sezione filo • Wire section <b>4,0 x 2,4</b>						
2S19025	98,0	6,3	613	9,4	919	25
2S19032	72,6	8,0	581	12,0	871	32
2S19038	56,0	9,5	532	14,3	798	38
2S19045	47,5	11,0	523	16,5	784	44
2S19050	41,7	12,8	532	19,1	798	51
2S19065	32,3	16,0	517	24,0	775	64
2S19075	25,1	19,0	477	28,5	715	76
2S19090	22,0	22,3	490	33,4	734	89
2S19101	19,8	25,5	505	38,3	757	102
2S19115	18,1	28,8	520	43,1	781	115
2S19126	16,6	31,8	527	47,6	791	127
2S19140	15,1	34,8	525	52,1	787	139
2S19151	13,2	38,0	502	57,0	752	152
2S19303	6,1	76,3	465	114,4	698	305
(D) Sede • Housing Ø mm 25 (d) Spina • Rod Ø mm 12,5						
Sezione filo • Wire section <b>5,3 x 3,1</b>						
2S26025	157,0	6,2	981	9,4	1472	25
2S26032	118,0	8,0	944	12,0	1416	32
2S26038	93,0	9,5	884	14,3	1325	38
2S26045	80,8	11,0	889	16,5	1333	44
2S26050	68,6	12,8	875	19,1	1312	51
2S26065	53,0	16,0	848	24,0	1272	64
2S26075	43,2	19,0	821	28,5	1231	76
2S26090	38,2	22,3	850	33,4	1275	89
2S26101	33,0	25,5	842	38,3	1262	102
2S26115	28,0	28,8	805	43,1	1208	115
2S26126	25,9	31,8	822	47,6	1233	127
2S26140	23,2	34,8	806	52,1	1209	139
2S26151	20,8	38,0	790	57,0	1186	152
2S26176	17,8	44,5	792	66,8	1188	178
2S26202	15,8	50,8	802	76,1	1203	203
2S26303	10,2	76,3	778	114,4	1167	305

Esempio d'ordine: Codice  
Order example:  
Bestellbeispiel:



Codice Cltg. No.	R Rigidità Rate N/mm	XLL 25%		Max 37.5%		L <sub>0</sub> Lungh. libera Free length mm
		S <sub>1</sub> Corsa Stroke mm	F <sub>1</sub> Carico Load N	S <sub>2</sub> Corsa Stroke mm	F <sub>2</sub> Carico Load N	
(D) Sede • Housing Ø mm 32 (d) Spina • Rod Ø mm 16						
Sezione filo • Wire section <b>6,8 x 4,0</b>						
2S32038	185,0	9,5	1758	14,3	2636	38
2S32045	158,0	11,0	1738	16,5	2607	44
2S32050	134,0	12,8	1709	19,1	2563	51
2S32065	99,0	16,0	1584	24,0	2376	64
2S32075	80,5	19,0	1530	28,5	2294	76
2S32090	69,1	22,3	1537	33,4	2306	89
2S32101	58,8	25,5	1499	38,3	2249	102
2S32115	51,5	28,8	1481	43,1	2221	115
2S32126	44,8	31,8	1422	47,6	2134	127
2S32140	42,3	34,8	1470	52,1	2205	139
2S32151	37,8	38,0	1436	57,0	2155	152
2S32176	32,5	44,5	1446	66,8	2169	178
2S32202	28,9	50,8	1467	76,1	2200	203
2S32252	22,2	63,5	1410	95,3	2115	254
2S32303	18,3	76,3	1395	114,4	2093	305
(D) Sede • Housing Ø mm 40 (d) Spina • Rod Ø mm 20						
Sezione filo • Wire section <b>8,1 x 4,8</b>						
2S38050	181,6	12,8	2315	19,1	3473	51
2S38065	140,0	16,0	2240	24,0	3360	64
2S38075	108,0	19,0	2052	28,5	3078	76
2S38090	90,7	22,3	2018	33,4	3027	89
2S38101	81,0	25,5	2066	38,3	3098	102
2S38115	71,8	28,8	2064	43,1	3096	115
2S38126	62,7	31,8	1991	47,6	2986	127
2S38140	57,5	34,8	1998	52,1	2997	139
2S38151	51,6	38,0	1961	57,0	2941	152
2S38160	47,5	40,0	1900	60,0	2850	160
2S38176	44,1	44,5	1962	66,8	2944	178
2S38202	36,7	50,8	1863	76,1	2794	203
2S38252	30,1	63,5	1911	95,3	2867	254
2S38303	24,6	76,3	1876	114,4	2814	305

Codice Cltg. No.	R Rigidità Rate N/mm	XLL 25%		Max 37.5%		L <sub>0</sub> Lungh. libera Free length mm
		S <sub>1</sub> Corsa Stroke mm	F <sub>1</sub> Carico Load N	S <sub>2</sub> Corsa Stroke mm	F <sub>2</sub> Carico Load N	
(D) Sede • Housing Ø mm 50 (d) Spina • Rod Ø mm 25						
Sezione filo • Wire section <b>10,9 x 6,0</b>						
2S51065	209,0	16,0	3344	24,0	5016	64
2S51075	168,0	19,0	3192	28,5	4788	76
2S51090	140,0	22,3	3115	33,4	4673	89
2S51101	119,0	25,5	3035	38,3	4552	102
2S51115	106,0	28,8	3048	43,1	4571	115
2S51126	97,0	31,8	3080	47,6	4620	127
2S51140	87,0	34,8	3023	52,1	4535	139
2S51151	80,0	38,0	3040	57,0	4560	152
2S51160	76,0	40,0	3040	60,0	4560	160
2S51176	69,5	44,5	3093	66,8	4639	178
2S51202	59,8	50,8	3035	76,1	4552	203
2S51229	50,9	57,3	2914	85,9	4371	229
2S51252	46,0	63,5	2921	95,3	4382	254
2S51303	38,6	76,3	2943	114,4	4415	305
(D) Sede • Housing Ø mm 63 (d) Spina • Rod Ø mm 38						
Sezione filo • Wire section <b>11,5 x 9,3</b>						
2S63075	320,0	19,0	6080	28,5	9120	76
2S63090	260,0	22,3	5785	33,4	8678	89
2S63101	221,0	25,5	5636	38,3	8453	102
2S63115	187,0	28,8	5376	43,1	8064	115
2S63126	168,0	31,8	5334	47,6	8001	127
2S63151	136,0	38,0	5168	57,0	7752	152
2S63160	128,0	40,0	5120	60,0	7680	160
2S63176	114,0	44,5	5073	66,8	7610	178
2S63202	100,0	50,8	5075	76,1	7613	203
2S63229	89,2	57,3	5107	85,9	7660	229
2S63252	78,4	63,5	4978	95,3	7468	254
2S63303	64,7	76,3	4933	114,4	7400	305
2S63315	62,8	78,8	4946	118,1	7418	315
2S63400	48,5	100,0	4850	150,0	7275	400

Esempio d'ordine: Codice  
Order example:  
Bestellbeispiel: